

Celltac ES

Automated Hematology Analyzer
MEK-7300

Extremely simple

WBC 5 part differential



Reliable

Enhanced statistics

- “Advanced Count*” for low PLT or WBC enhances reliability of low PLT or WBC.
- * When low PLT or WBC is detected, an additional sample is analyzed automatically.

Friendly

Stress-free simple operation

- Large color touch screen provides intuitive operation.
- Auto priming and self cleaning minimize start-up and shutdown time.

Efficient

Streamlined workflow

- Just 55 μ L sample aspiration for WBC 5 part differential
- 10 μ L/20 μ L can be measured with pre-dilution mode.
- Useful measurement modes:
Open, Closed, Pre-dilution, WBC high, and WBC low

made  Japan

Fighting Disease with Electronics
 **NIHON KOHDEN**

Specifications

Parameters	WBC, NE%, LY%, MO%, EO%, BA%, NE, LY, MO, EO, BA, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-CV, RDW-SD, PLT, PCT, MPV, PDW
Measurement methods	WBC, RBC, PLT – impedance method HCT – calculation from histogram HGB – cyanmethemoglobin optical detection WBC 5 part differential – optical method
Measurement modes	Open Closed Pre-dilution WBC high WBC low
Counting time	Approx. 60 sec/sample
Sample volume aspirated	55 µL (CBC + Diff), 30 µL (CBC) for normal measurement mode 10 or 20 µL for pre-dilution mode
Data storage	15,000 results including scattergrams and histograms can be stored on an SD card.
LCD display	10.4 inch 800 × 600 dots TFT-LCD
Dimensions	382 W × 465 D × 532 H (mm)
Weight	Approx. 35 kg

Reagents, Controls



Hematology control

MEK-5DN (normal) T456
MEK-5DL (low) T456L
MEK-5DH (high) T456H
(3 mL × 2 each)



Calibrator

MEK-CAL T457
(2mL)

Hemolyzing reagent for CBC

HEMOLYNAC-3N
Cyanide-free

Hemolyzing reagent for DIFF

HEMOLYNAC-5

Diluent

ISOTONAC-3

Detergent

CLEANAC

Detergent (Bleach)

CLEANAC-3

Option



SD card slot on the left side

Up to 15,000 results can be stored.

SD card
QM-001D
Y154D



Over 40 Years of Experience with In Vitro Diagnostic

Nihon Kohden launched its first automatic blood cell counter, MEK-1100 in 1972. Over the years, the models with more extensive and advanced capabilities are continually developed.



SD is a trademark of SD-3C, LLC.

This brochure may be revised or replaced by Nihon Kohden at any time without notice.



NIHON KOHDEN CORPORATION

1-31-4 Nishiochiai, Shinjuku-ku, Tokyo 161-8560, Japan
Phone +81 (3) 5996-8036 Fax +81 (3) 5996-8100
www.nihonkohden.com