

SPECIFICATIONS

THROUGHPUT

- Up to 266 tests / hour;
- Up to 180 photometric tests / hour in MONO mode.

REAGENT SYSTEM

- Refrigerated reagent rotor controlled with Peltier elements;
- Cooled to 10°C+/-2°C at normal laboratory conditions;
- 32 reagent positions for 10 ml, 25 ml and 50 ml reagent bottles;
- Reagent ID and automated programming of assays and calibrators via barcode;
- Typical reagent consumption 250 ul per test;
- All reagent positions can be assigned as R1, R2 and R3;
- Pre-heated needle with level detection, collision protection and integrated mixer.

SAMPLE SYSTEM

- Sample rotor containing:
 - Outer segment with 50 barcode readable positions
 - Inner segment with 12 auxiliary positions
 - All positions fit 13x75 mm primary and secondary tubes and pediatric cups
 - All positions can be used for Calibrators, Controls, Normal, Pediatric and STAT samples;
- Sample probe with level detection, integrated mixer and collision protection;
- Programmable dilution ratios 1:5 up to 1:200 in one step increments with 3 possible diluents.

PIPETTING SYSTEM

- 1000 µl Reagent syringe:
 - R1 volume 110 - 400 µl;
 - R2 volume 0 - 180 µl;
 - R3 volume 0 - 180 µl;
 - Programmable in 1 µl steps;
- 100 µl Sample syringe;
 - Sample volume 1-30 µl;
 - Programmable in 0.1 µl steps.

CUVETTE ROTOR

- Cost effective, semi-disposable cuvette rotor with 48 cuvettes, path length 7mm;
- >10.000 tests per rotor;
- Minimum measuring volume 220 µl;
- Measuring temperature 37°C, controlled by Peltier elements.

LIGHT SOURCE

- Quartz-iodine lamp 12V-20W.

WAVELENGTH RANGE

- 340 - 800 nm;
- Optical unit with 8 position filter wheel;
- Automatic wavelength selection
- 340, 405, 505, 546, 578, 620, 660, 700 nm standard installed;
- Other wavelnghts available on request.

PHOTOMETRIC RANGE

- -0.1 to 3.0 Absorbance;
- Resolution 0.001 Abs.

ANALYTICAL MODES (SINGLE, DUAL AND TRIPLE REAGENT SYSTEM)

- Kinetic measurement with linearity check;
- Mono- and bichromatic end point measurement with or without bichromatic reagent blank and/or sample blank correction;
- Two point measurement; with or without slope blank;
- Graphic plot of all measuring points;
- Predilution and automatic reflex dilution as needed;
- Non-linear calibration curves;
- Prozone check for immunology tests;
- Cut-off declaration;
- Calculated tests.

QUALITY CONTROL

- Up to 15 different controls can be defined, 3 per test;
- Westgard rules;
- Levey-Jennings plots;
- Quality control statistics.

WATER CONSUMPTION

- ~500 mL per hour max, continous operation.

STANDARDS AND REGULATIONS

- CE-IVD;
- CB.

DIMENSIONS (BENCHTOP, SELF CONTAINED UNIT)

- 122 x 75 x 61 cm (W x H x D);
- Weight: 95 kg.

INTERFACE

- Host: RS232 or Ethernet (TCP/IP) through LIS-2A protocol.

ENVIRONMENTAL CONDITIONS

- Temperature: 15 – 32 °C;
- Humidity: 15 – 85% RH;
- Altitude: up to 2000 m;
- Plumbing: No dedicated system water or drain required;
- Electrical:
 - Voltage: 100 – 240 Vac;
 - Frequency: 50 – 60 Hz;
 - Power (max): 380 VA.

INTEGRATED PC

- Operating System: MS Windows™ XP.

BAR CODE READER

- Hand held CCD bar code reader used for test requisition, reagent identification and automated programing of assasys, controls, and calibrators.

OPTIONS

DRY ELECTRODE ISE MODULE

- Patented Solid State Electrode Technology;
- Indirect Measurement
- Dilution 1:14;
- Measures Sodium, Potassium, Chloride and CO2.

POSITIVE SAMPLE IDENTIFICATION

- Positive Sample Identification (PSID) via integrated barcode reader. Reads all popular formats including Codes 39, 128, 11, 93, 4, CODABAR, and Interleaved 2/5.

PRINTER

- Printer supported by MS Windows™.

ECO KIT


- Enables separate collection of concentrated measurement mixture and dilute (wash) waste.

About ELITechGroup Clinical Systems...

ELITechGroup Clinical Systems is a global leader in BenchTop Chemistry Systems, with over 15,000 Chemistry Systems delivered.

Our mission is to enable better medical decisions by bringing high-value diagnostic solutions and services to laboratories that are closer to the patient (proximity laboratories).

ELITechGroup Clinical Systems leadership originates from our ability to continuously provide differentiated products and services focused to meet the needs of proximity laboratories. ELITechGroup Clinical Systems markets the Selectra Pro Series, designed to deliver trouble-free results laboratories can trust.



The Selectra Pro Series builds on the established robustness and reliability of the current Selectra systems, resulting from decades of proven experience in the design and manufacture of award winning BenchTop laboratory products. Together with a dedicated range of ready-to-use reagents from ELITech Clinical Systems, the Selectra Pro Series provides an ideal chemistry solution for laboratories that are closer to the patient.

Over the past decades, the ELITech Group Companies have established a solid distribution network that operates world-wide. Thousands of customers have experienced the quality, convenience and reliability of ELITech products. Local support is provided by dedicated and well trained sales and service organizations.

Distributor contact information:

Content of this document is subject to change without prior notification

Part nr: 6003-700-490-2014/02 EN

WORLDWIDE OFFICES

Headquarters
Australia
Benelux
Brazil
France
Italy
Middle East & Africa

T: +33 1 41 45 07 13
T: +61 1800 815 098
T: +31 313 430 574
T: +55 27 3025 1415
T: +33 4 83 36 10 82
T: +39 02 48 40 35 42
T: +971 4 375 2744

New Zealand
Serbia
Switzerland
The Netherlands
UK
United States

T: +64 800 555 611
T: +381 11 2467119
T: +41 26 663 86 60
T: +31 313 430574
T: +44 1442 869320
T: +1 609 216 7361

 **ELITechGroup**
SOLUTIONS
tailored to your needs
www.elitechgroup.com
info@elitechgroup.com

CLINICAL SYSTEMS

Selectra ProM



SELECTRA PRO
CHEMISTRY SYSTEM *M*

Delivery trouble free results Laboratories can trust

Selectra ProM™ is a trademark of ELITechGroup BV
Windows™ is a trademark of Microsoft

 **ELITechGroup**
CLINICAL SYSTEMS

Selectra ProM System

Setting the new standard in BenchTop Chemistry Systems, the Selectra ProM offers a robust new compact design, with best in class operator interface. New system features enable significant productivity and performance enhancements not typically found in BenchTop Chemistry Analysers.

Together with a superior menu of ready-to-use stable-liquid reagents from ELITech Clinical Systems, the new Selectra ProM System provides a state of the art, fully integrated chemistry solution for laboratories that are closer to the patient.



- ✓ New world class operator interface simplifies operation
- ✓ New compact integrated design - fully self contained including Command Center, ISE Module, reagent cooling, and on-board waste and water
- ✓ New productivity and error reducing capabilities: on-board PSID, Reagent ID and automated programming of assays, calibrators and controls
- ✓ New designs to improve performance, minimize maintenance and maximize uptime


Simplified operations with growing line of liquid-stable reagents

- ✓ Dedicated line of ready-to-use assays, packaged to fit the BenchTop laboratory
- ✓ Tied to proven methodologies, referenced and traceable to industry standards
- ✓ Standardized results across ELITechGroup Clinical Systems SELECTRA Family
- ✓ Commitment to ongoing enhancement to existing methods


Improved laboratories operations



Optimized with ELITechGroup Clinical Systems Reagents
When combined with the broad new ELITechGroup Clinical Systems test menu, the innovative system design increases the user-friendliness and efficiency of the Selectra ProM. The enhanced reagent supply provides flexibility in reagent containers and increased on-board stability. New features enable automated programming of assays, with bar coded reagents, calibrators and controls, streamlining operations and reducing error. Optimum sized packaging further enhances efficiency.



Integrated State of the Art Dry ISE Technology
Patented solid state electrodes have permanent gel which limits routine priming of ISE reference solutions as they can be left dry when not in use. This reduces reagent consumption and improves cost effectiveness. The Selectra ProM ISE design incorporates new control software and hydraulics which significantly enhances performance and reliability.



On-board PSID and data management features
PSID is one of the most effective productivity and error reducing capabilities in modern laboratory operations. The Selectra ProM brings on-board PSID to BenchTop Laboratories. Together with advanced data management features like our host-query LIS interface, versatile barcode based PSID eliminates the tedious job of programming samples and error prone matching of sample positions. Tests can be autovalidated versus laboratory defined parameters, improving walk-away operation and further increasing confidence in the results.



- New Designs to enhance performance, reliability, and reduce maintenance
- ✓ Improved level sensing and metering performance
 - ✓ Improved reagent thermal control
 - ✓ Longer life designs of key components reduces cost and cuts preventive maintenance service time in half
 - ✓ Improved method performance for TP, Magnesium and ISEs

Superior Test Menu*

General Chemistry	ALT/GPT, ALP , Amylase, AST/GOT, CK-MB, CK-NAC, GGT Plus, LDH-L
	Albumin, Bilirubin Direct, Bilirubin Total, Cholesterol, Cholesterol HDL, Cholesterol LDL, Creatinine, Glucose, Microprotein Plus, Total Protein Plus, Triglycerides, Urea UV, Uric Acid
	Calcium, Iron, Magnesium, Phosphorus
Specific Proteins	C-reactive Protein, Haptoglobin, HbA1C, IgA IP, IgG IP, IgM IP, Microalbumin, Orosomucoid, Prealbumin, Transferrin
Ion Selective Electrodes	Carbone Dioxide, Chloride, Potassium, Sodium

*Subject to regulatory clearance for some markets.

Simplicity that drives productivity

Best in Class Operator Interface

Selectra Systems are known for easy-to-use software, and the Selectra ProM sets a new standard for software navigation and operator interface. Touch screen operated with a next generation design, the state of the art software significantly boosts laboratory productivity.
The software is designed to have intuitive ease of use across a wide range of laboratory settings, from labs with basic IT to operations with fully automated informatics, from new operators to those with deep experience.
Intuitive icons guide the operator through their workflow and color coded graphic and audible alerts highlight conditions that operators need to know. Details are just a touch away.

Taking software to the next level
The intuitive simplicity designed into the software enables inexperienced staff to operate the Selectra ProM within an hour. Interactive routines lead the operator to the results quickly. Simplified operation brings new staff up to speed quickly, delivers continuous productivity improvements, and reduces errors.

- ✓ The unique combination of PSID, host-query LIS interface and programmable result checks dramatically improves walk-away time and reduces sample and test request entry and associated errors.
- ✓ Customizable start and end-of-day checklists guide operators through daily tasks, tracking upcoming maintenance, inventory on-board, and expiring calibrations and reagents.
- ✓ Operators' manual and system maintenance instructions are integrated in the software. Touch HELP on your daily checklist and the system links you directly to the instructions.
- ✓ To further optimize productive laboratory time, the system is capable of Remote Diagnostics, and will have software aided service adjustments and performance tests to maximize uptime.



THE NEW STATE OF THE ART IN BENCHTOP CHEMISTRY, SOFTWARE DESIGNED TO DELIVER TROUBLE FREE RESULTS LABORATORIES CAN TRUST